

RM200 HandHeld Diamond Coring



Easy to Use

- Progressive start switch
- Telescopic pilot pen centering (option),
- Integral vertical and horizontal spirit levels

Flexible

- 1/2" or 1 1/4" connections
- Hand held or rig mounted
- 3 speeds to suit specific coring diameters

Safe

- Mechanical clutch
- Thermal protection of motor

Specifications

Power Output	2000 W		
Speeds	No Load	Under Load	Diameter
1st speed	0-900 rpm	0-550 rpm	65-131 mm
2nd	0-2000 rpm	0-1250 rpm	32-50 mm
3rd	0-4000 rpm	0-2400 rpm	10-30 mm
Maximum Drilling Capacity (Wet)			131 mm
Weight			5.9 kg
Dimensions	559 x 365 x 140 mm		
Core Bit Connections	1/2" & 1 1/4"		
Insulation	Class II		

Dust Free Chasing



RW150E Chaser

- Quick Blade Fixing and Removal
- Variable width and depth of the cut
- Safe and ergonomic design
- Smooth start
- Close to edge operation
- Secure concrete face contact for straight cut

Dust Collection Vacuum

- Wet and dry vacuum
- Automatic filter vibrator
- Appliance activated start/stop
- Large capacity

Specifications	RW150E	Vacuum R1600-50
Power Output	2200 W	1600 W
Speed (no load)	8500 rpm	-
Weight	6 kg	11.5 kg
Chasing Width	up to 46.5 mm	-
Air Flow	-	64 L/S
Electric Cable	5 m	8 m
Suction Pipe	-	5 m/ø35 mm
Container Volume	-	50 L
Noise Level	-	70 Db
Size	-	40 x 40 x 56 cm