

ECAV Pipe/Tube Clip



Features & Benefits

- ECAV base clips easily onto the CableMaster pin guide from the side allowing one-handed operation.
- Raised mount position for pipe protection.
- Internal pipe supports absorb movement whilst maintaining flexibility.
- Fully encloses pipe for maximum support.
- Suits pipe outer diameters from 16 to 23mm.
- ECAV incorporates male/female connections for multiple clip installations side by side.
- Optional plug and screw installation for steel or timber studs.

Tube pull out loads at 22°C

Force required to manually remove tube from the clip

Tube Diameter (mm)	Average Ultimate Load (kg)	Working Load Limit, Tension (kg)
16-23	18	6

Technical Characteristics

Raw Material

- Nylon. Impact Resistant.
- Halogen free

Spacing Recommendation

- 0.5 and 1 metre (approx)

Fire Resistance Properties

- UL94HB fire test

Low Temperature Test

- No breakage at 0°C

ECAV Selection Guide

	SC6-20	HC6-22
Hard Concrete >50Mpa	●	○
Concrete <50Mpa	○	○
Hollow Concrete Block	○	○
Steel	○	●
Timber	○	○
Steel Decking	○	○

○ Suitable ● Possible

Product Description

ECAV 16-23mm CONTRACTOR PACK
400 x ECAV, *Pulsa* fuel cell
SC6 gas pins (20mm)

Order Qty

1

Order No

CPGCAV1623

INSTRUCTIONS FOR USE



1. Place the ECAV base on pin guide "off centre". Shift to the centre of the base until it "clicks" into position.



2. Place on work surface, depress the nozzle and fix the clip.



3. When fixed, it can be rotated around the pin to adjust its position.

Ramset recommends application tests on-site before commencing use.